

Declaration of Performance (DoP)										6060-T66
In compliance with EU regulation 305/2011, Annex III										
For the construction product										
1. Unique identification code of the product type:										
2. Type, batch or serial number or any other element allowing identification of the construction product in compliance with Article 11(4):										
3. Use(s) of the construction product intended by the manufacturer in compliance with the applicable harmonized technical specification:										
4. Name, registered trade name or registered trade mark and contact address of the manufacturer in compliance with Article 11(5):										
5. Name and contact address of the authorized representative commissioned with the tasks under Article 12 (2), if any:										
6. System(s) for assessment and verification of constancy of performance of the construction product in compliance with Annex V:										
7. If the declaration of performance concerns a construction product that is covered by a harmonized standard:										
8. If the declaration of performance concerns a construction product for which a European Technical Assessment was issued:										
9. Performance declared:										
Essential characteristics										Harmonized technical specification
Dimensional and shape tolerances										EN 755-9
Mechanical characteristics										
Flat profiles										
Wall thickness t (mm)										
Tensile strength R _m [MPa]										
min.										
max.										
Yield strength R _{p0.2} [MPa]										
min.										
max.										
Elongation A [%]										
min.										
max.										
Elongation A _{50mm} [%]										
min.										
max.										
HBW typical value										
min.										
max.										
Hollow profiles										
Wall thickness t (mm)										
Tensile strength R _m [MPa]										
min.										
max.										
Yield strength R _{p0.2} [MPa]										
min.										
max.										
Elongation A [%]										
min.										
max.										
Elongation A _{50mm} [%]										
min.										
max.										
HBW typical value										
min.										
max.										
Weldability										EN 1999-1
Bendability										EN 1999-1-3
Fatigue strength										EN 1999-1
Wear resistance										
Chemical composition										EN 573-3
Elements										
min										
max										
Elements										
min										
max										
10. The performance of the product according to numbers 1 and 2 is in accordance with the performance declared according to number 9. Only the manufacturer under 4 is responsible for preparing this declaration of performance.										

Signed for and on behalf of the manufacturer by:

Name and function:

Benoît DURET (Quality manager)

Place, date, signature:

Puget Sur Argens, 17/06/2025

