

Declaration of Performance (DoP)										6063-T5
In compliance with EU regulation 305/2011, Annex III										
For the construction product										
1. Unique identification code of the product type: EN AW-6063 T5/EN 755-9										Extruded aluminium sections
2. Type, batch or serial number or any other element allowing identification of the construction product in compliance with Article 11(4):										
3. Use(s) of the construction product intended by the manufacturer in compliance with the applicable harmonized technical specification:										Indoor and outdoor areas of load-bearing structures
4. Name, registered trade name or registered trade mark and contact address of the manufacturer in compliance with Article 11(5):										Hydro Extrusion Puget SAS ZA du Camp Dessert Nord – France 83488 Puget sur Argens Tel : +33 (0) 498112000 ; Fax : +33 (0) 494452344
5. Name and contact address of the authorized representative commissioned with the tasks under Article 12 (2), if any:										Not appointed
6. System(s) for assessment and verification of constancy of performance of the construction product in compliance with Annex V:										System 2+
7. If the declaration of performance concerns a construction product that is covered by a harmonized standard:										The notified body (DNV) performed the initial inspection of the manufacturing plant and of factory production control, as well as continuous surveillance, assessment and evaluation of factory production control in compliance with System 2+ and issue certificate 2388-CPR-07402 confirming conformity of the factory production control with the requirements set out in Annex ZA of EN 15088:2005 and 2388 – CPR – 22 – 095 – 17 conforming EN 1090-1
8. If the declaration of performance concerns a construction product for which a European Technical Assessment was issued:										Not applicable
9. Performance declared:										
Essential characteristics		Performance								Harmonized technical specification
Dimensional and shape tolerances		In compliance with standard								EN 755-9
Mechanical characteristics		In compliance with standard								
Flat profiles										
Wall thickness t (mm)	Tensile strength R _m [MPa]	min.	max.	Yield strength R _{p0.2} [MPa]		Elongation A [%]	Elongation A _{90mm} [%]	HBW typical value		
				min.	max.					
				min.	max.					
≤ 10	175	NPD	130	NPD	8	6	65			
10 < t ≤ 25	160	NPD	110	NPD	7	5	65			
Hollow profiles										
Wall thickness t (mm)	Tensile strength R _m [MPa]	min.	max.	Yield strength R _{p0.2} [MPa]		Elongation A [%]	Elongation A _{90mm} [%]	HBW typical value		
				min.	max.					
				min.	max.					
≤ 55	175	NPD	130	NPD	8	6	65			
Weldability		Class I								EN 1999-1
Bendability		B3								
Fatigue strength		NPD								EN 1999-1-3
Wear resistance		Table 3.1a								EN 1999-1
Chemical composition	Elements	Si	Fe	Cu	Mn	Mg	Cr	Ni	Zn	
		min	0.20	-	-	0.45	-	-	-	
		max	0.60	0.10	0.10	0.9	0.10	-	0.10	
Elements	Ti	Ga	V	Other (each)	Other (total)	Al	Rest	Remark		
	min	-	-	-	-	-	-	-		
	max	0.1	-	-	0.05	0.15	-	-		
10. The performance of the product according to numbers 1 and 2 is in accordance with the performance declared according to number 9. Only the manufacturer under 4 is responsible for preparing this declaration of performance.										

Signed for and on behalf of the manufacturer by:

Name and function:

Place, date, signature:

Benoît DURET (Quality manager)

Puget Sur Argens, 17/06/2025

